


# MPP6--BLACK-72 CELL



## 18.0%

PANEL EFFICIENCY


## 10 YEAR

PRODUCT WARRANTY

## 0 - 5W

POWER TOLERANCE

### 25 Years Linear Warranty



# Specification

## MP Solar Panel

Independently tested for proven product quality and long-term reliability. Millions of PV systems installed worldwide demonstrate MP industry leadership.



#### Durability

Durable PV modules, independently tested for harsh environmental conditions such as exposure to salt mist, ammonia and known PID risk factors.



#### Advanced Glass

Our high-transmission glass features a unique anti-reflective coating that directs more light on the solar cells, resulting in a higher energy yield.



#### Extended Size

Our large-format module facilitates system-level cost savings through reduced handling and installation times.



#### PID Resistant

Tested in accordance to the standard ISO9001–2008, our PV modules have demonstrated resistance against PID (Potential Induced Degradation), which translates to security for your investment.

# MPP6-- 72 CELL SERIES

## ELECTRICAL PERFORMANCE

Module type								
Power output	$P_{max}$	W	330	335	340	345	350	
Power output tolerances	$P_{max}$	W						
Module efficiency	$\eta_m$	%	17.0	17.2	17.5	17.7	18.0	
Voltage at $P_{max}$	$V_{mp}$	V	37.8	38.0	38.2	38.4	38.6	
Current at $P_{max}$	$I_{mp}$	A	8.73	8.82	8.91	8.99	9.07	
Open-circuit voltage	$V_{oc}$	V	46.1	46.3	46.5	46.8	47.0	
Short-circuit current	$I_{sc}$	A	9.24	9.32	9.4	9.49	9.58	

STC: 1000W/m<sup>2</sup> irradiance, 25°C module temperature, AM1.5g.

## THERMAL CHARACTERISTICS

Nominal operating cell temperature	NOCT	°C	44 +/- 2
Temperature coefficient of $P_{max}$	$\beta_{P_{max}}$	%/°C	-0.41
Temperature coefficient of $V_{oc}$	$\beta_{V_{oc}}$	%/°C	-0.31
Temperature coefficient of $I_{sc}$	$\beta_{I_{sc}}$	%/°C	0.05

## OPERATING CONDITIONS

Max. system voltage	1000VDC or 1500 VDC
Max. series fuse rating	15A
Limiting reverse current	20A
Operating temperature range	-40°C to 85°C
Max. static load, front (e.g., snow)	5400Pa
Max. static load, back (e.g., wind)	2400Pa
Max. hailstone impact (diameter / velocity)	25mm / 23m/s

## CONSTRUCTION MATERIALS

Front cover (material / thickness)	low-iron tempered glass / 3.2mm
Cell quantity / material	(6*12) = 72 / monocrystalline silicon
Dimensions / number of busbars	156.75mm x 156.75mm / 5BB
Frame (material)	Silvery, anodized aluminum alloy
Junction box (protection degree)	IP67
Cable (length / cross-sectional area)	TUV, 1000mm / 4mm <sup>2</sup>
Plug connector	MC4

- Due to continuous innovation, research and product improvement, the specifications in this product information sheet are subject to change without prior notice. The specifications may deviate slightly and are not guaranteed.
- The data do not refer to a single module and they are not part of the offer, they only serve for comparison to different module types.

## CERTIFICATION



**Jiangsu MP New Energy Co.,Ltd**



## GENERAL CHARACTERISTICS

Dimensions(L/W/H)	1956mm/992mm/40mm
Weight	22.5kg

## PACKAGING SPECIFICATIONS

Number of modules per pallet	27
Number of pallets per 20' container	10
Number of modules per 20' container	270
Number of pallets per 40' container	24
Number of modules per 40' container	648

## DIMENSIONS OF PV MODULE(mm)



Warning: Read the Installation and User Manual in its entirety before handling, installing, and operating SPV Solar modules.

Jiangsu MP New Energy CO.,LTD

[info@mpsolarlife.com](mailto:info@mpsolarlife.com)

[mpsolarlife@outlook.com](mailto:mpsolarlife@outlook.com)

Mobile/Whatsapp: +86 18352781668

[www.mpsolarlife.com](http://www.mpsolarlife.com)